

Instantaneous frequency and amplitude identification using wavelets: Application to glass structure

J. D. Harrop, S. N. Taraskin and S. R. Elliott*
*Department of Chemistry, University of Cambridge,
Lensfield Road, Cambridge CB2 1EW, United Kingdom.*

PACS numbers: 02.70.Hm, 61.43.Fs, 02.30.Nw, 61.43.Bn

We regret that it has come to our notice that some typographical errors appeared in the paper [1] in the description of the new mother wavelet function and associated normalization expressions.

The correct expressions for the mother wavelet function are (the equation numbers refer to those in the original paper):

$$\psi(t; \sigma) = e^{-t^2/2} \{p(\sigma) [\cos(\sigma t) - \kappa(\sigma)] + iq(\sigma) \sin(\sigma t)\} \quad (5)$$

$$p(\sigma) = \pi^{-1/4} (1 + 3e^{-\sigma^2} - 4e^{-3\sigma^2/4})^{-1/2} \quad (6a)$$

$$q(\sigma) = \pi^{-1/4} (1 - e^{-\sigma^2})^{-1/2}. \quad (6b)$$

The variance of the Gaussian approximation to the envelope of the mother wavelet is:

$$\sigma_\psi^2(\sigma) = \frac{1}{4} \sqrt{\pi} \left\{ q^2 \left[1 + (2\sigma^2 - 1) e^{-\sigma^2} \right] + p^2 \left\{ \left[1 + (3 - 2\sigma^2) e^{-\sigma^2} \right] - 2(2 - \sigma^2) e^{-3\sigma^2/4} \right\} \right\}. \quad (11)$$

With this formulation, the remainder of the paper is correct and all results are unaffected.

Acknowledgments

We are grateful to Victor P. Ostanin for pointing out the mistake.

-
- [1] J. D. Harrop, S. N. Taraskin, and S. R. Elliott, Phys. Rev. E **66**, 026703 (2002).

*Electronic address: jdh30@cam.ac.uk; URL: <http://www.chem.pwf.cam.ac.uk/~jdh30>